



THE WINNING FORMULA.

NEWXUS
f(P+R)

Brunswick 

© 2012 Brunswick Bowling & Billiards Corporation. Item #10-095300-078 • Form #1211-08

NEXXUS™ *f*(P+R)

PP[®]
Pro Performance

ADDAPTIVE *f*(P+R) SOLID COVERSTOCK

The **Addaptive *f*(P+R) Solid** coverstock is Brunswick's newest innovation in performance enhancing additive chemistry. *f*(P+R) describes our latest formula that combines our new (P)rojection and our new (R)ecovery additives together to create our most aggressive coverstock to date. The Projection additive easily pushes the super aggressive coverstock down lane where the Recovery additive connects with the lane for an extraordinary backend hook motion. Being able to combine multiple additives in a coverstock allows Brunswick to effectively fine tune the length, mid-lane and backend characteristics of the ball.

CORE

The new **Nexus Rotor** core integrates a center stabilizing capsule and two vertical flip claws. The center stabilizing capsule revs quickly to control the mid-lane. As the axis migrates and the core lays down, the vertical flip claws take over maintaining the rev rate for a strong continuation through the backend and powerful drive through the pins.

BALL MOTION

The **Nexus *f*(P+R)** is so strong it extends the limits of our Ball Comparison chart. With its 1500-grit Siaair micro pad finish, the **Nexus *f*(P+R)** offers our highest hook potential and most continuation of any Brunswick ball to date.

With an extraordinary ball motion the **Nexus *f*(P+R)** skids through the front, saves axis rotation in the mid-lane and grabs the backend for unbelievable continuation on medium to heavy oil lane conditions.

REACTION SETUP

The **Nexus *f*(P+R)** can be drilled using the standard drilling techniques developed for asymmetric bowling balls.

LIGHTWEIGHT ENGINEERING

At Brunswick, the unique core shape of each individual ball is used for weights from 14 to 16 pounds. This approach to lightweight ball engineering provides bowlers with consistent ball reaction characteristics across this weight range. At 12 and 13 pounds, Brunswick uses a generic core shape with a RG-differential that is close enough to the 14 to 16 pound shape so the same drilling instructions can be used.



SPECIFICATIONS

Hook Potential	Low(10)	<input type="range" value="200"/>	High(200)
Length	Early(25)	<input type="range" value="110"/>	Long(235)
Breakpoint Shape	Smooth Arc(10)	<input type="range" value="100"/>	Angular(100)
RG Differential	Low(0)	<input type="range" value="0.056"/>	High(.060)
RG Average	Center Heavy(1)	<input type="range" value="3.1"/>	Cover Heavy(10)

- Nexus Rotor Core
- Addaptive *f*(P+R) Solid Coverstock
- 2- Color, Red and Black Solid
- Hardness: 73-75
- 500 & 1,500 Siaair Micro Pad Finish
- Chart Position: Y-2
- Part No. 60-105440-93X



16 LB 15 LB 14 LB 13 LB 12 LB

RG-MAX	2.524	2.536	2.553	2.632	2.655
RG-INT	2.507	2.519	2.536	2.621	2.644
RG-MIN	2.468	2.480	2.497	2.589	2.612
RG-DIFF	0.056	0.056	0.056	0.043	0.043
RG-ASY	0.017	0.017	0.017	0.011	0.011

NEXXUS
f(P+R)

Brunswick[®]
BowlwithBrunswick.com